

NUMAX XV FOCUS





ACOUSTICAL SPECIFICATION

Amplitude linearity (± 3 dB) (*)	50 - 20 000 Hz	(*) with #HPF 50 Presets
Operating frequency range (- 6dB)	43 - 20 000 Hz	
Cut off frequencies (- 10dB)	37 - 20 000 Hz	
Number of ways	2	
Sensitivity (LF)	97 dB	
Sensitivity (LC/MHF)	97 dB	
Maximum SPL (LF) (*)	140 dB	(*) Peak level at 1-meter under free field conditions using 12 dB crest factor pink noise
Maximum SPL (LC/MHF) (*)	140 dB	(*) Peak level at 1-meter under free field conditions using 12 dB crest factor pink noise
Horizontal coverage	100°	
Vertical coverage	10°	

TECHNICAL SPECIFICATIONS

Nominal impedance (LF)	8 Ω	
Nominal impedance (LC/MHF)	8 Ω	
AES power handling (LF)	1 000 W	
AES power handling (LC/MHF)	1 000 W	
Peak power handling (LF)	4 000 W	
Peak power handling (LC/MHF)	4 000 W	
Transducer (LF)	1 x 15" driver with neodymium magnet	
Transducers (LC)	2 x 8" driver with neodymium magnet	
Transducer (MF)	1 x 8" driver with neodymium magnet	
Transducer (HF)	1 x 2.85" neodymium compression driver (*)	(*) Voice Coil Diameter
Enclosure type (LF)	Bass-Reflex	
Enclosure type (LC)	Passive radiator (1 x 8")	
Crossover type	Active (FIR)	

PHYSICAL SPECIFICATIONS

Height	17.2 in (436 mm)
Width	37.4 in (950 mm)
Depth	21.0 in (534 mm)
Weight	121 lbs (55 kg)
Enclosure angle	10°
Connectors	2 x speakON NL4MP
Handles	4
Rigging	Compatible with NUMAX XV Wide, NUMAX BUMP, LYRE NUMAX and LIFTBAR NUMAX



REFERENCES

NUMAX XV Focus	High-efficiency 2-way cardioid array loudspeaker, with constant curvature (1 x 15" LF ; 1 x 8" MF ; 1 x 2.85" HF ; 2 x 8" LC ; 1 x 8" PR) and featuring MHF waveguide optimized for 10° vertical dispersion
BUMP NUMAX	Bumper for Amadeus NUMAX XV Focus/Wide and NUMAX SUB provided with two shackles
LYRE NUMAX	U-Bracket for one Amadeus NUMAX XV Focus/Wide/Extra Wide or one NUMAX SUB
LIFTBAR NUMAX	Vertical lifting bar for Amadeus NUMAX XV Focus, Wide and Extra Wide models
TOOLCASE NUMAX XV	System technician toolkit including display, inclinometer sensor and >5mw Class 3R 532nm laser units
FA1NUMAXXVFOCUS	Flight Case featuring casters with brakes for one Amadeus NUMAX XV Focus
FA2NUMAXXVFOCUS	Flight Case featuring casters with brakes for two Amadeus NUMAX XV Focus
9005	Jet Black finish for cabinet, based on RAL 9005 color
9010	Pure White finish for cabinet, based on RAL 9010 color
1013	Oyster White finish for cabinet, based on RAL 1013 color
7040	Window Grey finish for cabinet, based on RAL 7040 color
7030	Stone Grey finish for cabinet, based on RAL 7030 color
5011	Steel Blue finish for cabinet, based on RAL 5011 color
9005	Jet Black color for Airtex [®] acoustical fabric, based on RAL 9005 color
9006	White Aluminium color for Airtex [®] acoustical fabric, based on RAL 9006 color
9010	Pure White color for Airtex [®] acoustical fabric, based on RAL 9010 color
1035	Pearl Beige color for Airtex [®] acoustical fabric, based on RAL 1035 color
1036	Pearl Gold color for Airtex [®] acoustical fabric, based on RAL 1036 color



STANDARD COLOR CODES

Amadeus systems offer a standard 'Jet Black' finish, based on RAL 9005 color. The following codes allow you to select separately the colors associated with the different external elements that Amadeus systems are composed of.

REFERENCE / **** 1 / **** 2

**** 1 RAL COLOR CODES FOR CABINETS AND MECHANICAL ELEMENTS

**** 2 RAL COLOR CODE FOR AIRTEX[®] ACOUSTICAL FABRIC

For example, a two-color PMX 5 MKII system with 'Jet Black' cabinet (RAL 9005) and 'White Aluminium' Airtex[®] fabric in front of the protection grid (RAL 9006) gets the code PMX5MKII/9005/9006. Another example, a single-color DIVA XS system, made with a 'Pure White' (RAL 9010) cabinet and mechanical elements and a 'Pure White' (RAL 9010) acoustical fabric Airtex[®] covering the protection grid gets the code DIVAXS/9010/9010.

Please contact us if you want to order any specific color.

HIGHLY RESISTANT FINISH (HRF)

Amadeus recently invested in a new painting area featuring new painting machines able to produce a high-resistance resin-based finish, making the speakers highly resistant to scratches, shocks and water projections.

This new optional finish, increasing the systems' durability as well as the degree of protection provided by enclosures against intrusion, dust, accidental contact, and water up to IP55 (EN 60 529) is now available available on-demand.

Please contact us if you want to order any specific finish.

ACCESSORIES TO MEET YOUR NEEDS

Accessories are often the forgotten detail. They are, however, a vital component in a complex speaker setup.

To compliment our core product offering, we also provide an extensive range of accessories.

The selection of accessories includes a huge number of mounting and connecting accessories, available to accommodate any configuration of installation.

The key to our success is to remain flexible. We have a unique manufacturing programme which allows us to efficiently produce anything from small batches to an automated production process for large scale manufacturing.

Please contact us if you want to order any specific accessory.

